

07

FOG MACHINE

Accessories ————— p23



Lower the temperature for the earth .(energy-conservation lowers the temperature, reduces carbons, environment protection)popularize the movement of "loving the earth"



Nozzle

Part No.	Size Dia/Ψ mm	core ditchxmm	Male Thread T	Spring size (mm)	Opear Pres Kg/cm2	Flow Valume c.c./Min	diameter mm	Length mm	Weight g
D01	0.15	2x0.2	No.10/24nuc	0.55x6.5	30~70	28~48	9.5	22	8.5
D02	0.20	2x0.2	No.10/24unc	0.55x6.5	30~70	48~73	9.5	22	8.5
D03	0.30	2x0.3	No.10/24unc	0.55x6.5	30~70	60~110	9.5	22	8.5

- 1.Stainless steel spray production using Japan 316 stainless steel.It can abrasion and resistance chemical pH.
- 2.Spray piece the perforation thickness than 0.2MM. This type of nozzle is the thickest.
- 3.Nozzle design are removable and easy to replace or clean.



UV PROTECTION TUBE



TUBE CUTTER



DYP-6600



QUICK FITTING



Nail Cable Clip



PRESSURE GAUGE



FAUCET ADAPTOR



KJ-50H (GAUGE)

Weight 6KG
Length30CM
Wide15CM
Height19CM
Voltage 110V (50/60HZ)
Voltage 220V (50/60HZ)
With controller timer



KJ-15H

Weight 5KG
Length30CM
Wide15CM
Height19CM
Voltage 110V (50/60HZ)
Voltage 220V (50/60HZ)
Without controller timer

A great deal of trades that the restaurant, coffee shop, tea art house, amusement park, factory, courtyard, greenhouse, domestic animal give up, ect.. Its range of application is quite extensive, every profession and trade can be planned, application in accordance with the demand.(May match "CLO2"deodorizes sterilization)the demand.(May match "CLO2"deodorizes sterilization)

